

MG GP GREASE

GENERAL PURPOSE GREASE
NLGI # 0, 1, 2, 3, 4



Performance Profile

MG GP GREASE is a good quality, smooth-textured, Calcium base general purpose grease, formulated with highly refined base stocks, Calcium soap thickener and balanced additive package. Exceeds the requirements of :

DIN 51502 K1C, K2C, K3C, K4C
DIN 51825 K1B, K2B, K3B, K4B
ISO L-XBADA1, L-XBADA2, L-XBADA3, L-XBADA4

Application

Suitable for the lubrication of vehicle chassis, water pump, farm, workshop and construction-site machineries and other services, when water-resistant is an important consideration.

Summary of Benefits

- Fair structural stability.
- Better protection against rust, corrosion and wear.
- Good resistance to oxidation.
- Non corrosive to all metals.
- Outstanding ability to resist water washout.

Technical Data

Characteristics	Typical Value				
	0	1	2	3	4
NLGI consistency	0	1	2	3	4
Range of use, °C	-20 to 52	-20 to 52	-20 to 52	-20 to 52	-20 to 52
Dropping point , °C	80	90	90	90	95
Worked penetration @ 25 °C, dmm	370	325	280	235	190

FRP Services reserves the right to change the information given herein without prior notice. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume liability for occurrence arising out of its use. The user, by accepting products described herein agrees to be responsible for thoroughly testing any application before committing to production.



FRP SERVICES & COMPANY
1-15-9 Awaza, Nishi-ku, Osaka 550-0011, Japan
TEL:+81-6-6535-1933 FAX:+81-6-6535-1675
www.frp-services.com