

MG GEAR OIL LP

MODERATE PERFORMANCE GEAR OIL
SAE 90, 140



Performance Profile

MG GEAR OIL LP is a good quality oil formulated with highly refined base stocks and antifoam additive package. Exceeds the requirements of :

API GL-1

Application

Suitable for manual transmissions, spiral bevel and worm axles and all gearing systems used in automotive vehicles and off-the-road equipments, operating under mild-service conditions of low unit pressure and sliding velocities.

Summary of Benefits

- Natural thermal and oxidation stability.
- Good protection against wear, foaming, rust and corrosion.
- Harmless to all metals and gaskets.
- Good demulsibility power.
- Good protection of bearing and gear teeth.

Technical Data

Characteristics	Typical Value	
	90	140
Sp. Gravity @ 15°C	0.901	0.913
Viscosity @ 40 °C, cSt	220	460
Viscosity @ 100°C, cSt	19	31
Viscosity Index	97	95
Flash Point, COC, °C	268	292
Pour Point, °C	-6	-6

FRP Services reserves the right to change the information given herein without prior notice. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume liability for occurrence arising out of its use. The user, by accepting products described herein agrees to be responsible for thoroughly testing any application before committing to production.



FRP SERVICES & COMPANY

1-15-9 Awaza, Nishi-ku, Osaka 550-0011, Japan

TEL:+81-6-6535-1933 FAX:+81-6-6535-1675

www.frp-services.com