

MG Hydraulic OIL AW

SUPER PERFORMANCE HYDRAULIC OIL
ISO 32, 46, 68, 100, 150



Performance Profile

MG HYDRAULIC OIL AW is a top quality oil with high degree of wear protection, designed with highly refined base stocks and well balanced additive package. Exceeds the requirements of :

Denison HF-O including
dry & wet T6C-020

U.S. Steel 126 / 127

Vickers M-2950-S
(Mobile equipment)

DIN 51524 Part II

Vickers 1-286-S3
(Industrial equipment)

AFNOR NF E 48-603 (HM)

Cincinnati Milacron
P-68, P-69 & P-70.

ASLE 64-1 to 64-4, 70-1 to 70-3

Application

Recommended for high pressure hydraulic systems used in all mobile and stationary equipments, operating under severe working conditions. Also used for circulation system, compressor, pump, bearing and gear lubrication where recommended.

Summary of Benefits

- Extended oil life.
- Outstanding thermal and hydrolytic stability.
- Excellent demulsibility power and air release capability.
- Outstanding filterability and good shear stability.
- Exceptional resistance to oxidation and foaming.
- Highly effective controlover wear, corrosion and rust.
- Low pour point ensures good fluidity in cold climates.
- Improved compatibility with seals and soft metals.
- Improved friction characteristics resulting in lower running temperatures.



Technical Data

Characteristics	Typical Value				
	32	46	68	100	150
Sp. Gravity @ 15°C	0.874	0.877	0.879	0.882	0.889
Viscosity @ 40 °C, cSt	33	45	67.5	99.5	144
Viscosity @ 100°C, cSt	5.5	6.70	8.7	11.3	14.5
Viscosity Index	102	101	100	99	98
Flash Point, COC, °C	220	224	232	236	248
Pour Point, °C	-12	-9	-9	-9	-6
Pump Tests	Pass	Pass	Pass	Pass	Pass
4 - Ball Wear Test (15 kg/ 80°C /600 rpm/2 hrs)	Pass	Pass	Pass	Pass	Pass

FRP Services reserves the right to change the information given herein without prior notice. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume liability for occurrence arising out of its use. The user, by accepting products described herein agrees to be responsible for thoroughly testing any application before committing to production.



FRP SERVICES & COMPANY
 1-15-9 Awaza, Nishi-ku, Osaka 550-0011, Japan
 TEL:+81-6-6535-1933 FAX:+81-6-6535-1675
www.frpservices.com