

MG MP GREASE

HEAVY DUTY GREASE
NLGI # 0, 1, 2, 3, 4



Performance Profile

MG MP GREASE is a high quality, smooth-textured, Lithium base multipurpose grease, designed with highly refined base stocks, Lithium complex thickener and balanced additive package. Exceeds the requirements of :

DIN 51502 KL1K, KL2K, KL3K, KL4K
DIN 51825 KL1K, KL2K, KL3K, KL4K
ISO L-XBCDA1, L-XBCDA2, L-XBCDA3, L-BCDA4

Application

Recommended for the efficient lubrication of plain and rolling element bearings, joints, couplings, linkages, pivots and all other mechanical parts used in automotive, industries, mining, marine and other services, subject to intense mechanical loads and thermal stresses. Also suitable for centralized lubrication systems.

Summary of Benefits

- Outstanding protection against wear, rust and corrosion.
- Excellent structural stability to resist excessive softening or hardening as a result of shearing.
- Controlled oil bleeding to supply small amount of oil needed to form EHL film.
- Non corrosive to all metals.
- Reinforced ability to resist water washout.
- Effective resistance to centrifuging and oxidation at high service temperature.
- Excellent choice to simplify stock-control.

Technical Data

Characteristics	Typical Value				
NLGI consistency	0	1	2	3	4
Range of use, °C	-20 to 130	-20 to 130	-20 to 130	-20 to 130	-20 to 130
Dropping point , °C	175	185	185	185	190
Worked penetration @ 25 °C, dmm	370	325	280	235	190

FRP Services reserves the right to change the information given herein without prior notice. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume liability for occurrence arising out of its use. The user, by accepting products described herein agrees to be responsible for thoroughly testing any application before committing to production.



FRP SERVICES & COMPANY
1-15-9 Awaza, Nishi-ku, Osaka 550-0011, Japan
TEL:+81-6-6535-1933 FAX:+81-6-6535-1675
www.frp-services.com