

MG Spiral 205

SUPER PERFORMANCE MOTOR OIL
SAE 15W/40, 15W/50, 20W/50



Performance Profile

MG SPIRAL 205 is a premium quality oil formulated with highly refined base stocks and well balanced additive package. Exceeds the requirements of :

API SF/CC	CCMC G2/D1
Mil-L-46152C	MB 226.1
Russian Oil Specifications -	
M-5z/12G1 & M-6z/14G1	

Application

Especially recommended for the lubrication of heavy-duty, turbocharged or atmospheric gasoline and diesel engines used in passenger cars and some trucks, operating under severe-service.

Summary of Benefits

- Better fuel economy.
- Reinforced thermal behavior.
- Super fluidity at low temperature ensures good starting.
- Excellent resistance to oxidation, foaming, low temperature sludge and high temperature deposits.
- Efficient control over wear, rust and corrosion.
- Excellent detergent and dispersant qualities.

Technical Data

Characteristics	Typical Value		
	15W/40	15W/50	20W/50
Sp. Gravity @ 15°C	0.866	0.889	0.893
Viscosity @ 40 °C, cSt	110	145	170
Viscosity @ 100°C, cSt	14.5	19	19
Viscosity Index	135	145	120
Flash Point, COC, °C	220	230	248
Pour Point, °C	-30	-30	-27
TBN, mgm KOH / gm	5.6	5.6	5.6

FRP Services reserves the right to change the information given herein without prior notice. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume liability for occurrence arising out of its use. The user, by accepting products described herein agrees to be responsible for thoroughly testing any application before committing to production.



FRP SERVICES & COMPANY
1-15-9 Awaza, Nishi-ku, Osaka 550-0011, Japan
TEL:+81-6-6535-1933 FAX:+81-6-6535-1675
www.frp-services.com