

MG Spiral 209

MODERATE PERFORMANCE MOTOR OIL
SAE 10W, 30, 40 , 50, 20W/40, 20W/50



Performance Profile

A good quality oil formulated with highly refined base stocks and a balance additive package. Exceeds the requirements of :

API SB/CB

Mil-L-2104A , Supplement 1

Application

Suitable for the lubrication of naturally aspirated gasoline and diesel engines used in passenger cars and some trucks, operating under mild-service.

Summary of Benefits

- Natural thermal stability.
- Good resistance to foaming and corrosion.
- Mild antiwear capability and resistance to oil oxidation.
- Mild detergency and dispersions.

Technical Data

| Characteristics | Typical Value | | | | | |
|------------------------|---------------|-------|-------|-------|--------|--------|
| | 10W | 30 | 40 | 50 | 20W/40 | 20W/50 |
| Sp. Gravity @ 15°C | 0.876 | 0.882 | 0.889 | 0.901 | 0.884 | 0.893 |
| Viscosity @ 40 °C, cSt | 38 | 103 | 160 | 220 | 140 | 170 |
| Viscosity @ 100°C, cSt | 6 | 11.50 | 15.50 | 19 | 15.5 | 19 |
| Viscosity Index | 102 | 99 | 98 | 97 | 111 | 120 |
| Flash Point, COC, °C | 220 | 236 | 254 | 268 | 242 | 248 |
| Pour Point, °C | -12 | -9 | -6 | -6 | -15 | -27 |
| TBN, mgm KOH / gm | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 |

FRP Services reserves the right to change the information given herein without prior notice. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume liability for occurrence arising out of its use. The user, by accepting products described herein agrees to be responsible for thoroughly testing any application before committing to production.



FRP SERVICES & COMPANY

1-15-9 Awaza, Nishi-ku, Osaka 550-0011, Japan

TEL:+81-6-6535-1933 FAX:+81-6-6535-1675

www.frpservices.com