MG UNIVERSAL TRACTOR OIL All ROUND PERFORMANCE OIL SAE 10W/30

Performance Profile



MG UNIVERSAL TRACTOR OIL is a top quality multipurpose oil with innovative conception, designed with highly refined base stocks and specially selected complete additive package. Surpassing the requirements of :

API CD/SE CCMC D2/G1 Mil-L-2105C Ford M2C-159B Massey Ferguson M-1139 Denison HF-2

Application

Satisfies the lubrication requirements of all types of engines, as well as wet brakes, hydraulic systems, automatic and manual transmissions used in farm and industrial tractors and self-propelled farm equipments. Not recommended when manufacturers specify an EP oil of API GL-5 level.

Summary of Benefits

- Very high viscosity index.
- Outstanding lubrication power in all working conditions.
- Excellent fluidity at low temperature.
- Exceptional thermal and oxidation stability at high temperature.
- Improved retention of frictional properties to resist chatter and squawk in clutch and brake systems.
- Outstanding protection against rust, corrosion and foaming.
- Effective antiwear and extreme-pressure properties to protect the gear teeth and bearings.
- Improved seals compatibility.
- Superior filterability and stability in the presence of water.
- Right level of detergency to ensure a clean system.
- Excellent choice to reduce the possibility of wrong applications.

Technical Data

| Characteristics | Typical Value |
|------------------------|---------------|
| | 10W/30 |
| Sp. Gravity @ 15°C | 0.881 |
| Viscosity @ 40 °C, cSt | 51 |
| Viscosity @ 100°C, cSt | 9.4 |
| Viscosity Index | 150 |
| Flash Point, COC,°C | 220 |
| Pour Point, °C | -33 |
| TBN, mgm KOH / gm | 9.8 |

FRP Services reserves the right to change the information given herein without prior notice. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume liability for occurrence arising out of its use. The user, by accepting products described herein agrees to be responsible for thoroughly testing any application before committing to production.



FRP SERVICES & COMPANY 1-15-9 Awaza, Nishi-ku, Osaka 550-0011, Japan TEL:+81-6-6535-1933 FAX:+81-6-6535-1675 www.frpservices.com